



A&TTM



SNAP 4K

USB WIDE ANGLE CAMERA

Applications: Huddle room | Small conference room | Hybrid class room



4K ULTRA HD



AUTO FOCUS
LENS



BUILT-IN
MICROPHONE



LOW LIGHT



SNAP 4K

SPECIFICATION



Camera

Sensor	1/2.5", CMOS, Effective Pixel: 8M
Scanning Mode	Progressive
Lens 1	Focus: f=2.8mm, FOV: 120°
Autofocus	Support
Minimal Illumination	0.05 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Digital Noise Reduction	2D, 3D digital noise reduction
Backlight Compensation	Support

Input / Output Interface

USB Port	1xUSB 3.0: Type B, female
HDMI Interface	1xHDMI: Version 1.4

USB Features

Operate System	Windows® 7, 8, 10 or higher & macOS™ 10.10 or higher Google™ Chromebook™ Version 29.0.1547.70 or higher Linux (UVC support is required)
Hardware Requirement	2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB 2.0 port (USB 3.0 required for 4K)
Video Format	4k@30fps/25fps, 1080p@60fps/50fps/30fps/25fps, 720p@60fps/50fps/30fps/25fps, 960x540p@60fps/50fps/30fps/25fps, 640x360p@60fps/50fps/30fps/25fps
Color System / Compression	H.265 / H.264 / MJPEG
USB Video Communication Protocol	UVC 1.0 ~ UVC 1.5
UVC PTZ	Support(EPTZ)

General Information

Input Voltage	5V (USB power supply)
Operating Temperature	'-10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	'-40°C ~ 60°C (-40°F ~ 140°F)
Size	194mm x 34mm x 42mm (without bracket)