



# JARVIS U2e

Full HD Video Conferencing Camera


**Applications:** Conference room | Hybrid class room



FULL HD  
1080 P




12X ZOOM



FOV 72.5°



ENHANCED PTZ



USB & HDMI



MAKE IN INDIA



# JARVIS U2e

## SPECIFICATION



### Camera

Image Sensor	1/2.8inch CMOS
Min Lux	0.1Lux(F1.2)
Effective Pixel	3.10 Mega Pixels
Zoom	12X Optical
Shutter Speed	1 to 1/10000s
Field of View	72.5°
Resolution	1080P60/50, 1080P30/25, 1080i60/50, 720P60/50
Focus Mode	Auto
Aperture Mode	Auto
Backlight Compensation	Support
Wide Dynamic	Support
Picture Adjustment	Brightness, Chroma, Saturation, Contrast, Acutance
Minimum Illumination	0.1 lux
Signal System	PAL/NTSC
Gain	Auto/Manual
Preset Position	9 Preset Positions by IR Remote Controller
Image Effect	Full Color / Black & White / Electronic Flip
S/N Ratio	≥50DB
SNR	65.5dB

### Interface

Video Interface	USB 2.0, HDMI
Video Compressed Format	MJPEG/H.264
Control Interface	RS-232/485/USB Control
Control Agreement	VISCA/PELCO-D/PELCO-P
Communicate Baud Rate	2400/4800/9600/11520/19200/38400
Power Interface	DC 12V

### PTZ

Pan Rotation	-170°~ +170°
Tilt Rotation	-30°~ +90°
Horizontal Rotate Speed	0.1~100°/second
Vertical Rotate Speed	0.1~80°/ second

### Others

Power Adapter	Input AC100V~AC240V Output DC12V/2A
Input voltage	DV12V
Power Consumption	12W(MAX)
Storage Temperature	-20°C ~ +60°C
Working temperature	0°C ~ +40°C
Operating Environment	Indoor
Color	Silver
Weight	1525g

\*OPTIONAL ACCESSORIES - WALL MOUNT, CEILING MOUNT, CABLES